

Pneumatic Stapler Type 42/38-159

Wherever it is necessary to fasten thin, soft material such as paper, cardboard, plastic, foil to wood or other materials, this stapler is a must.

The powerful BeA 42/38-159 drives flat wire staples of type 42 with a wide crown (24.2 mm) in the lengths of 14 to 38 mm.

The comfortable rubber grip and the attached exhaust make this well-balanced tool operator friendly.



Popular applications:

Packaging, butt-joints, cabinets, fastening of roofing felt etc.

Length: 371 mm
Width: 70 mm
Height: 261 mm

Technical data

Type description:	42/38-159 Standard
Article code:	12000180
Magazine type :	Top loader
Safety:	Contact
Fastener type:	Typ 42
Magazine capacity:	148
Fasteners per strip:	4x 37
Operating pressure:	6 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	1.5 litres / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d = 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d = 87 dB
Weight:	0.94 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 4.0 m/s²

Extras supplied with the stapler: Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Article code	Description
14403409	Remote valve with safety yoke
14403402	Remote valve, complete
14403442	Mounting flange
14400899	High adjustable stop
14406201	Single actuation set

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive
for Machinery (89/392 EWG)

Product leaflet 159

Pneumatic Stapler Type 42/38-159

Staples type 42



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: +49 (0) 4102 78-0
Fax: +49 (0)4102 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG

Description	L = Length mm
42/14 NK	14
42/16 NK	16
42/19 NK	19
42/22 NK	22
42/25 NK	25
42/30 NK	30
42/35 NK	35
42/38 NK	38

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut