

## Pneumatic Stapler Type 380/16-429 LN

A variation of the successful upholstery stapler 380/16-420. The 50 mm long nose allows for ease of entry into those “hard-to-get-to” places. Outstanding features of this stapler are: low weight, high penetration power as well as integrated silencer and low air consumption.



### Popular applications:

Car and caravan industry, upholstered furniture and case goods manufacture

Length:	221 mm
Width:	43 mm
Height:	192 mm

### Technical data

Type description:	380/16-429 LN
Article code:	12000073
Magazine type :	Bottom loader
Safety:	-
Fastener type:	Type 80 / 380
Magazine capacity:	157
Fasteners per strip:	1 x 100 type 80 / 1 x 150 type 380
Operating pressure:	5 – 6 bar
Max. operating pressure:	6 bar
Air consumption/operation:	0.3 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 79 dB
Single-shot emission sound pressure level:	L WA, 1 s, d= 87 dB
Weight:	1.03kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

### Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

### Accessories:

Article code	Description
14403330	Remote valve, compl.
14406168	Back nose assembly set 6 mm. Please note on your orders.

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive  
for Machinery (89/392 EWG)

Product leaflet 429LN


## Pneumatic Stapler Type 380/16-429 LN

Staples type 80 and type 380



BeA Deutschland  
Befestigungstechnik  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: +49 (0) 4102 78-0  
Fax: +49 (0) 4102 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG



Description	L = Length mm
380/06 NK	6
380/08 NK	8
380/10 NK	10
380/12 NK	12
380/14 NK	14
380/16 NKS	16

Other lengths and finishes are also available on request.

### Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut