

# Pneumatic Plier

## Type 380/16-419

The BeA Pneumatic Plier 380/16-419 guarantees secure of a variety of materials. The pressure of the clinching jaw is controlled so that the work material is gently pressed against prior to the staple being driven. The deep jaw throat allows fastening even in hard to reach area.

The plier drives staples type 80/380 in the length of 6 to 16 mm.



### Popular applications:

Clinching of: Paper, cardboard, foil, leather, bag headers etc.

Length: 210 mm  
 Width: 50 mm  
 Height: 216 mm

### Technical data

Type description:	<b>380/16-419</b> Standard
Article code:	12000062
Magazine type :	Bottom loader
Safety:	Type 80 / 380
Fastener type:	160
Magazine capacity:	1 x 150
Fasteners per strip:	5 – 6 bar
Operating pressure:	6 bar
Max. operating pressure:	0.7 liters / 6 bar
Trigger frequency:	Ø 9 mm LW recommended
Air consumption/operation:	L pA, 1s, d= 86 dB
Inner hose diameter:	L WA, 1 s,d= 92 dB
Emission sound pressure level at the workstation:	1.4 kg
Single-shot emission sound pressure level:	
Weight:	

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

<b>Extras supplied with the stapler:</b>	Operating instructions, spare parts list, service instructions, allen keys SW 8, SW 13, silencer.
	Subject to technical modifications.

### Accessories:

Article code	Description
14406013	Carton support
14400437	Back nose assembly set (6 mm)
14403705	Back nose assembly set (Standard)
14405273	Jaw with 100 mm insertion depth

All BeA pneumatic tools can be jig-mounted  
 We supply the necessary accessories and equipments.



This tool conforms to the EG Directive for Machinery (89/392 EWG)


## Pneumatic Stapler Type 380/16-419

Staples type 80 and type 380



BeA Deutschland  
Befestigungstechnik  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: (04102) 78-0  
Fax: (04102) 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG



Description	L = Length mm
380/06 NK	6
380/08 NK	8
380/10 NK	10
380/12 NK	12
380/14 NK	14
380/16 NKS	16

Other lengths and finishes are also available on request.

**Explanations:**

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut