

Multifix Nailer Type TC 300

The light weight BeA Multifix drives common plastic sheet collated nails from 60 – 100 mm and plastic sheet collated anchor nails Ø 4,0 from 40 – 100 mm.

For the metal connector fastening the special designed nose attachment easily locates every hole. The multi-impact mechanism provides sufficient power.



Popular applications:

Metal connectors, roof truss, faming, heavy duty packing and crating

Length: 385 mm
Width 128 mm
Height: 195 mm

Technical data

Type description:	TC 300
Article code:	12100007
Magazine type :	Coil magazine / side loader
Fastener type:	TC
Magazine capacity:	50
Nails per coil:	1 x 50
Operating pressure:	6– 8bar
Max. operating pressure:	8bar
Air consumption/operation:	4,25 litre / 6 bar
Inner hose diameter:	Ø 13 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 96 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 107 dB
Weight:	2.2 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 2.55 m/s²

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions
For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)





Multifix Nailer Type TC 300



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: +49 (0) 4102 78-0
Fax: +49 (0)4102 78-250
www.bea-group.com
e-mail: info@bea-group.com

Anchor nails type TC

Coil nail type TC



a division of
Joh. Friedrich Behrens AG

Description	L = Length mm
TC- Anchor nails 4,0 x 40 NK Ring*	40
TC- Anchor nails 4,0 x 50 NK Ring*	50
TC- Anchor nails 4,0 x 60 NK Ring*	60
TC- Anchor nails 4,0 x 75 NK Ring*	75

TC 2,8 x 60 NK Ring*	60
TC 2,8 x 65 NK Ring*	65

TC 2,8 x 65 BK	65
TC 3,1 x 75 BK Ring	75
TC 3,1 x 90 BK Ring	90
TC 3,4 x 100 BK	100
TC 3,8 x 100 BK	100

* Nails are certified to DIN 1052 Part 2
Other lengths and finishes are also available on request.



Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut