

Pneumatic Stapler Type 97/16-407

The light but powerful stapler of the 400 series takes staples type 97 in leg lengths from 6 mm to 16 mm. The low air consumption, long service life and ease of maintenance of this stapler make it a real cost saver. The bottom loading magazine allows easy and quick loading. Further features are the ergonomic design and the integrated silencer. This is a versatile tool for industry and the craftsman.



Popular applications:

Upholstered furniture, chairs, TV and stereo cabinets, loudspeakers, wicker and rattan furniture, perambulators, automobile industry

| | |
|---------|----------|
| Length: | 210,5 mm |
| Width: | 40 mm |
| Height: | 141 mm |

Technical data

| | |
|---|------------------------------|
| Type description: | 97/16-407 Standard |
| Article code: | 12000048 |
| Magazine type : | Bottom Loader |
| Safety: | - |
| Fastener type: | Type 97 |
| Magazine capacity: | 100 |
| Fasteners per strip: | 1 x 100 |
| Operating pressure: | 5 – 6 bar |
| Max. operating pressure: | 6 bar |
| Air consumption/operation: | 0.3 litre / 6 bar |
| Inner hose diameter: | Ø 9 mm LW recommended |
| Emission sound pressure level at the workstation: | L pA, 1s, d= 82 dB |
| Single-shot emission sound pressure level: | L WA, 1 s,d= 87 dB |
| Weight: | 0.9 kg |

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

Accessories:

| Article code | Description |
|--------------|--|
| 14400590 | Screw cap with balancer eye |
| 14400827 | Adjustable roller edge guide (assembly in factory) |
| 14400870 | Sole attachment |
| 14403535 | Mounting flange |
| 14400674 | Screw cap, Alu |
| 14403330 | Remote valve, complete |

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Stapler Type 97/16-407

Staples type 97



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



| Description | L = Length mm |
|-------------|------------------|
| 97/06 NK HZ | 6 |
| 97/08 NK HZ | 8 |
| 97/10 NK HZ | 10 |
| 97/12 NK HZ | 12 |
| 97/14 NK HZ | 14 |
| 97/16 NK HZ | 16 |

Other lengths and finishes are also available on request.

Explanations:

| | | | |
|------------------------------------|--------------------------------|--|----------------------|
| NK = galvanized steel | BK = bright steel | LM = aluminium | HZ = resin coated |
| NKS = galvanized steel, extra hard | BKS = bright steel, extra hard | NR = stainless steel, material. 1.4401 | DP = divergent point |
| NKH = galvanized steel, hard | MS = brass | RF = rust resistant, material 1.4301 | SA = step cut |