

Pneumatic Bradder Type SK 218-411

The small and lightweight bradder SK 218 –411 drives very thin brad nails type SK 200 with diameter 0.8mm from 15 to 18mm. The special formed nose allows working at narrow working places.

The nails' heads are brown, but can be ordered in other colors as well as without color.



Popular applications:

Glazing strips, rosettes, trim, moulding, ornaments.

Length: 205 mm
Width: 40 mm
Height: 149 mm

Technical data

Type description:	SK 218-411 Standard
Article code:	12000053
Magazine type :	Side loader
Safety:	-
Fastener type:	Brads type SK 200
Magazine capacity:	168
Fasteners per strip:	2 x 75
Operating pressure:	5 – 6 bar
Max. operating pressure:	6 bar
Air consumption/operation:	0.3 litre / 6 bar
Inner hose diameter:	Ø 6 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 82 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB
Weight:	1.01 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer.
For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Articel code	Description
14400590	Screw cap with eye hook
14403330	Remote valve, complete
14403535	Mounting flange
14400674	Screw cap, Alu

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Bradder Type SK 218-411

Brads type SK 200



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



Description	L = Length mm
SK 215 NK	15
SK 218 NK	18

The SK 200 finish nail heads are coloured brown (standard).
Other colours are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut