

Pneumatic Bradder Type SK 451 – 717

The BeA Pneumatic Bradder SK 451-717 drives finish nails in the length from 25 to 51 mm. The top loading device guarantees quick and safe loading. The nails can be delivered in a variety of head-colours as well as in stainless steel.

The available accessories make the SK 451-717 even more versatile.



Popular applications:

Glazing strips, wicker work, furniture, corner trims, molding, chair rail, cabinetry.

Length:	231mm
Width:	70 mm
Height:	227 mm

Technical data

Type description:	SK 451-717	
	Contact	
Article code:	12000256	
Magazine type :	Top loader	
Safety:	Contact actuation	
Fastener type:	Finish nails SK 400	
Magazine capacity:	97	
Fasteners per strip:	2 x 40	
Operating pressure:	5 – 8 bar	
Max. operating pressure:	8 bar	
Air consumption/operation:	0.9 litre / 6 bar	
Inner hose diameter:	Ø 9 mm LW recommended	
Emission sound pressure level at the workstation:	L pA, 1s, $d=82 \text{ dB}$	
Single-shot emission sound pressure level:	L WA, 1 s,d= 91 dB	
Weight:	2.15 kg	

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 3.0 m/s²

Extras supplied with the nailer:	Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.
	Subject to technical modifications.

Articel code	Description	
14403421	Remote valve	
14403536	Mounting flange	
14406172	Exhaust set	

All BeA pneumatic tools can be jig-mounted We supply the necessary accessories and equipments.




This tool conforms to the EG Directive for Machinery (89/392 EWG)



Pneumatic Bradder Type SK 451-717

SK 400 finish nails



Description E = Delign mm Mm SK 425 NK 25 SK 428 NK 28 SK 432 NK 32 SK 435 NK 35
SK 428 NK 28 SK 432 NK 32
SK 432 NK 32
SK 435 NK 35
SK 438 NK 38
SK 441 NK 41
SK 445 NK 45
SK 448 NK 48
SK 451 NK 51

SK 432 NR *	32
SK 435 NR *	35
SK 438 NR *	38

The SK 400 finish nail heads are coloured brown (standard). Other lengths and finishes are also available on request. * only without colour



BeA Deutschland Befestigungstechnik P.O.Box 14 80 D-22904 Ahrensburg Phone: (04102) 78-0 Fax: (04102) 78-250 www.bea-group.com e-mail: info@bea-group.com

a division of Joh. Friedrich Behrens AG

$\mathbf{F}_{\mathbf{v}}$	plan	ofic	met	
ĽA	Jian	au	ль.	

Explanations.			
NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut