

# Pneumatic Bradder Type SK 338 – 616

A lightweight and particularly well balanced tool. The BeA Pneumatic Bradder SK 338-616 drives finish nails in the length from 22 to 38 mm. The top loading device guarantees quick and safe loading. The nails can be delivered in a variety of head-colours as well as in stainless steel.

The available accessories make the SK 338-616 even more versatile.



#### **Popular applications:**

Glazing strips, wicker work, furniture, corner trims.

Length:	231 mm
Width:	57 mm
Height:	200 mm

#### **Technical data**

Type description:	SK 338-616	SK 338-616 E Single	
	Contact		
Article code:	12000225	12000227	
Magazine type :	Top loader	Top loader	
Safety:	Contact actuation	Single actuation	
Fastener type:	Finish nails SK 300	Finish nails SK 300	
Magazine capacity:	125	125	
Fasteners per strip:	1 x 100	1 x 100	
Operating pressure:	5 – 8 bar	5 – 8 bar	
Max. operating pressure:	8 bar	8 bar	
Air consumption/operation:	0.9 litre / 6 bar	0.9 litre / 6 bar	
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended	
Emission sound pressure level at the workstation:	L pA, 1s, d= 84 dB	L pA, 1s, d= 84 dB	
Single-shot emission sound pressure level:	L WA, 1 s,d= 89 dB	L WA, 1 s,d= 89 dB	
Weight:	1.6 kg	1.6 kg	


The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

### Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this. Subject to technical modifications.

Accessories:	
Articel code	Description
14400816	Glazier Stop
14403421	Remote valve
14403527	Mounting flange
14403428	Remote valve with additional manual actuation
14406951	Grip elongation
All BoA proumatic tools can be iig mounted	This tool conforms to the EC Directive

All BeA pneumatic tools can be jig-mounted






This tool conforms to the EG Directive for Machinery (89/392 EWG)

## Product leaflet 616



# Pneumatic Bradder Type SK 338-616

SK 300 finish nails



Description	L = Length	
Description	mm	
SK 322 NK	22	
SK 325 NK	25	
SK 330 NK	30	
SK 335 NK	35	
SK 338 NK	38	
SK 335 NR *	35	

The SK 300 finish nail heads are coloured brown (standard). Other lengths and finishes are also available on request. \* only without colour



BeA Deutschland Befestigungstechnik P.O.Box 14 80 D-22904 Ahrensburg Phone: (04102) 78-0 Fax: (04102) 78-250 www.bea-group.com e-mail: info@bea-group.com

a division of Joh. Friedrich Behrens AG

### **Explanations:**

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut