



26°Angled Brad Nailer Type SK AM 350-226C

Description

One of the first 18 gauge angled brad nailers

with an ergonomic, durable, light weight tool design. Best tool balance to reduce operator fatigue.

Especially made for easy and accurate nail

Fastening applications :

Attachment of decorative sealing strips, ornaments, rosettes, glazing strips, trim, moulding, chair rails....

Technical Data:

Technical Dala.					
Type description:	SK SM 350-226C				
Article code:	12100233				
Nail type:	26°, 18 gauge				
Magazine type:	Rear loader				
Magazine capacity:	120				
Cycles per second:	10				
Mode of operation, standard:	Contact actuation				
Weight, kg:	1,37				
Dimension L/W/H, mm:	288/63/260				
Brads per strip:	100				
Brads wire size Ø mm:	1,25x1,0				
Brads range length, mm:	20,25,32,38,45,50				
Operating pressure, bar:	5-8				
Max. operating pressure, bar:	8				
Air consumption/operation, bar:	1,4				
Inner hose diam. recomm.,mm:	9-10				
Single-shot emission sound pressure level: L _{WA, 1s, d}	86				
Emission sound pressure level at the workst.: L _{pA, 1s, d}	80				
Vibrations: m/s2	3,1				
C: 6: +:					

Specification:

Œ

Tool, tool case, service oil, operating-/service instructions, spare parts list, allen wrenches 3mm- 4mm, blister pack with 3 Mille Brads(20,30,50,)

This tool conforms to the EG directive for Machinery (98/37 EC).





Tool case included





Joh. Friedrich Behrens AG POB 1480 D-22904 Ahrensburg Germany Phone: +49 (0) 4102 78-0 Fax: +49 (0) 4102 78-250 www.bea-group.com info@bea-group.com



26º magazine: Exact placement of brads. No marks on sensitive surfaces.



26º magazine: Narrow working places always visible, even in corners and angles.



26º Brads Head size: 2,0x1,4mm

Head height: 1,0mm

Shank Ø: 1,25x1,0mm



Tray

Carton

Article-Description	ArtNo.	Packaging units							
		Box		Tray		Carton		Pallet	
		Mille	kg	Mille	kg	Mille	kg	Mille	kg
Tool SK AM 350-226C	12100233								
SK AM 320 NK	10300487	3	0,60	30	6,00	60	12,0	4.800	960
SK AM 325 NK	10300488	3	0,75	30	7,50	60	15,0	3.600	900
SK AM 332 NK	10300489	3	0,95	30	9,50	60	19,0	3.600	1.140
SK AM 338 NK	10300490	2	0,72	20	7,25	40	14,5	2.880	1.044
SK AM 345 NK	10300491	2	0,85	20	8,50	40	17,0	2.560	1.088
SK AM 350 NK	10300492	2	0,92	20	9,25	40	18,5	2.560	1.184

SKAM350-226C-EN-LL.doc 17.07.2006