

Pneumatic Plier Type 195/25-526

The BeA Pneumatic Plier 195/25-526 guarantees secure of a variety of materials from 5 to 45 mm. The pressure of the clinching jaw is controlled so that the work material is gently pressed against prior to the staple being driven. The plier drives staples type 195 in the length of 15 to 25 mm.



Popular applications:

Clinching of: cardboard, bag headers, poster coverings, closing of buckets

Length: 324 mm
Width: 57 mm
Height: 359 mm

Technical data

Type description:	195/25-526 Standard
Article code:	12000150
Magazine type :	Top loader
Fastener type:	Type 195
Magazine capacity:	135
Fasteners per strip:	2 x 63
Operating pressure:	5 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	0.83 liters / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d = 76 dB
Single-shot emission sound pressure level:	L WA, 1 s,d = 83 dB
Weight:	1.74 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the plier: Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Plier Type 195/25-526



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: +49 (0) 4102 78-0
Fax: +49 (0) 4102 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG

Staples type 195



Description	L = Length mm
195/15 NK	15
195/18 NK	18
195/21 NK	21
195/25 NK	25

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut