

Pneumatic Bradder Type SK 445-618

A lightweight and particularly well balanced tool. The BeA Pneumatic Bradder SK 445-618 drives finish nails in the length from $28\ to\ 45$ mm. The top loading device guarantees quick and safe loading. The nails can be delivered in a variety of head-colours as well as in stainless steel.

The available accessories make the SK 445-618 even more versatile.



Popular applications:

Glazing strips, wicker work, furniture, corner trims, molding, chair rail, cabinetry.

231 mm Length: Width: 57 mm Height: 200 mm

Technical data

Type description:	SK 445-618		
	Contact		
Article code:	12000254		
Magazine type:	Top loader		
Safety:	Contact actuation		
Fastener type:	Finish nails SK 400		
Magazine capacity:	97		
Fasteners per strip:	2 x 40		
Operating pressure:	5 – 8 bar		
Max. operating pressure:	8 bar		
Air consumption/operation:	0.9 litre / 6 bar		
Inner hose diameter:	Ø 9 mm LW recommended		
Emission sound pressure level at the workstation:	L pA, 1s, d= 84 dB		
Single-shot emission sound pressure level:	L WA, 1 s,d= 89 dB		
Weight:	1.6 kg		

Extras supplied with the nailer:	Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.
	Subject to technical modifications.

A	C	C	es	S	()	'n	es	;

Article code	Description
14400816	Glazier Stop
14403421	Remote valve
14403527	Mounting flange
14403428	Remote valve with additional manual actuation
14406951	Grip elongation



Pneumatic Bradder Type SK 445-618

SK 400 finish nails



BeA Deutschland Befestigungstechnik P.O.Box 14 80 D-22904 Ahrensburg Phone: (04102) 78-0 Fax: (04102) 78-250 www.bea-group.com e-mail: info@bea-group.com

a division of Joh. Friedrich Behrens AG

3	1,0
L	_28
1,63	45 x 1,42

	1
Description	L = Length
	mm
SK 428 NK	28
SK 432 NK	32
SK 435 NK	35
SK 438 NK	38
SK 441 NK	41
SK 445 NK	45

SK 438 NR *	38

The SK 400 finish nail heads are coloured brown (standard). Other lengths and finishes are also available on request.

* only without colour

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut