

## Pneumatic Tacker Type BCS 31-193

This very specialized stapler drives round crown divergent point staples type 150. A special “grooved” version of this staple is also available in which the staple diverge outward for better holding power. There are two versions of the BCS 31-193 tool, steel and aluminum. Steel for less recoil and aluminum for easier overall handling. The nose has a clearing slot for easy jam clearance.



### Popular applications:

Bedding ( springs to frame build-ups).

Height: 920 mm  
Width: 48 mm  
Length: 403 mm

### Technical data

Type description:	BCS31-193 Steel housing	BCS31-193 Aluminum housing
Article code:	12000323	12000433
Magazine type :	Top loader	Top loader
Fastener type:	Type 150/19	Type 150/19
Magazine capacity:	173	173
Fasteners per strip:	3 x 47	3 x 47
Operating pressure:	5 – 6 bar	5 – 6 bar
Max. operating pressure:	6 bar	6 bar
Air consumption/operation:	1,4 litre / 6 bar	1,4 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 75 dB	L pA, 1s, d= 75 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 84 dB	L WA, 1 s,d= 84 dB
Weight:	3,3 kg	2,7 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

### Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

### Accessories:

Articel code	Description

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive  
for Machinery (89/392 EWG)

## Pneumatic Tacker Type BCS 31 -193

Staple type 150/19 UC



BeA Deutschland  
Befestigungstechnik GmbH  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: (04102) 78-0  
Fax: (04102) 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)



Description	L = Length mm
150/19 UC	19
150/19 UC Groove	19

Other lengths and finishes are also available on request.

### Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut