

## Hotmelt Applicator BeA 285

The **BeA 285** is a trigger actuated professional electric glue gun, offering a high glue output up to 1,2 kg per hour. It is ergonomically designed for many hours of continual use and ideal for high-speed work.

An important feature of the **BeA 285** is the adjustable temperature. With the enclosed screwdriver it is easily possible to change the temperature to vary between 140° and 220° C. The tool is designed to use standard 12mm glue sticks.

The advantages of the economic melt-on-demand system are also found in the **BeA 285**.



Length: 290 mm  
Width: 55 mm  
Height: 230 mm

### Technical data

Type description:	<b>BeA 285</b>
Article code:	12500149
Voltage, power consumption:	220 V, 220 W
Melt rate:	up to 1.2 kg / hour
Initial warm up time:	approx. 5 minutes
Melting time after reloading:	0 seconds
Temperature control:	thermostat – adjustable from 140 – 220°
Feed mechanism:	Mechanical
Weight:	600 g

### Extras supplied with the gun:

Operating instructions, 2.2 m cable, removable wire stand, extra nozzle, plastic-case.

Subject to technical modifications.

# Hotmelt Applicator BeA 285



BeA Deutschland  
Befestigungstechnik  
POB 1480  
22904 Ahrensburg  
Germany  
Phone: (04102) 78-0  
Fax: (04102) 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG

## Hotmelt adhesives for BeA 285 (Nominal diameter 12 mm, length 190/200\* mm)

Article Code	Description	Typical characteristics and applications
11800220	HM 535/12 F*	Clear; high viscosity; relatively short open time; good adhesion to a wide range of materials

Packaging units: 10 kg per carton = 5 bags á 2 kg, 350\*/360 kg per pallet

## More hotmelt adhesives (Nominal diameter 12 mm, length 200 mm)

11800221	HM 505/12*	Packaging adhesive; fast setting; rigid, firm bond
11800061	HM 640/12	Clear; general purpose; excellent adhesion to a wide range of materials; excellent adhesive performance
11800062	HM 642/12	General purpose; excellent adhesion to a wide range of materials such as wood, wood products and plastic; colour: beeswax.
11800064	HM 660/12	Excellent adhesion even on critical materials such as glass, metal, plastic,; very elastic, impact resistant bond

Packaging units 5 kg per carton, 500 kg per pallet  
\*10 kg per carton = 5 bags á 2 kg, /360 kg per pallet

## Explanations:

HM = ethylene vinyl acetate based hotmelt adhesive

## Polyamide – hotmelt for wood - repair

Hotmelt	Temperature
PA 813/12 Semi-Transparent, Off White, Ivory, Beige, Amber	175° C
PA 134-1/12 Dark Brown	195° C
PA 134-2/12 Light Brown	
PA 817/12 Black	
PA 162/12 Dark Brown	220° C
PA 162/12 Transparent	
PA 817/12 “Cola”	

For detailed information on the individual adhesives, please refer to the respective technical data sheets.  
Other hotmelt adhesives for special applications are also available upon request.