

Pneumatic Stapler Type P8/16-428 for plastic staples

The light but powerful stapler of the 420 series takes plastic staples type P8 in leg lengths from 8 mm to 16 mm. The low air consumption, long service life and ease of maintenance of this stapler make it a real cost saver. The bottom loading magazine allows easy and quick loading. Further features are the ergonomic design and the integrated silencer. This is a versatile tool for industry and the craftsman.

For all applications where normally aluminum staples are used.



Popular applications:

Barcodes for wooden products, e.g. fences, windows, doors; caravans, boats.

Length: 221 mm
Width: 43 mm
Height: 148 mm

Technical data

Type description:	P8/16-428 Standard	P8/16-428 Safety
Article code:	12000358	12000359
Magazine type :	Bottom loader	Bottom loader
Safety:	-	Safety yoke
Fastener type:	Plastic staples	Plastic staples
Magazine capacity:	76	76
Fasteners per strip:	1 x 70	1 x 70
Operating pressure:	5 – 6 bar	5 – 6 bar
Max. operating pressure:	6 bar	6 bar
Air consumption/operation:	0.3 litre / 6 bar	0.3 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 79 dB	L pA, 1s, d= 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB	L WA, 1 s,d= 87 dB
Weight:	0.95 kg	0.95 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories :

Article code	Description
14403330	Remote valve compl.
14405424	Screw cap Alu

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Stapler Type P8/16-428

Plastic staples



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



Description	L = Length mm
P 8/10	10
P 8/15	15

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut